

Logger ThinLog




Measure the temperature of your processes and products

°C
°F

Thermal mapping and Heat Penetration

PU / Fo calculations to core product

Ideal with low thickness packaging



Logger ThinLog



Measure the temperature of your processes and products

Specificities

- Very easy** to use in mapping
- Fully** maintenance free
- Service life:** 3 to 5 years upon frequency of use
- Meets direct food** contact standards

Applications

- Monitoring** of thermal processes: retort, sterilizer, tunnel, oven, ...
- Temperature** of retort or packaged product
- Cold spot / hot spot** location in thermal equipment
- Perfectly suited** for flat and thin packaging
- Runs with **AXITHERM** communication interfaces and softwares

Performances

- Measures temperature** without disturbing the environment
- Weight of** 5,2 g for a volume of 1,9 cm³
- 3 temperature ranges:** -40 to +85°C / 0 to +125°C / +15 to +140°C
- Reduced dimensions:** Ø 19,8 x 6,2 mm
- Full scale accuracy** better than ± 0.15 °C
- Watertightness:** IP 68 from -1 to 7 bar
- Memory capacity:** 4096 data
- 3 recording modes:** immediate - date / time - temperature thresholds



AXITHERM SARL

35 FONTEVRAULT STREET - 72200 LA FLÈCHE - FRANCE

Phone : +33 243 960 378

Email : contact@axitherm.com - www.axitherm.com

capital of 15245€, RCS of LE MANS 44100455300026 – code APE 8299 Z

N° VAT FR 19 441 004 553

